

MAX STONE

ACRYLIC SEALER & FINISH

Product # 031

DESCRIPTION

Do not worry anymore about the deterioration of floors and general surfaces exposed and/or subjected to heavy wear and traffic. We have developed the most effective acrylic polymer sealer in the industry just to protect your floors from the damage caused by these elements. One coat of Max Stone provides the gloss, sheen and protection usually achieved with two or more coats of ordinary sealers. Economical, quick-drying formula. Reduces down time and inconvenience. Recommended for commercial, institutional, educational and industrial use wherever there are floors or surfaces to be protected from penetration of spills or subjected to heavy traffic.

DIRECTIONS

Completely strip all old wax or finish. Rinse thoroughly. Be sure all old finish is removed and surface is dry and completely stripped. Apply MAX STONE in a uniform thin coat. Allow 30 minutes for drying. Apply a second coat if desired.

DAILY MAINTENANCE

Dust mop or sweep as necessary. Maintain traffic areas by dry buffing, burnishing, spray buffing or re-coat as necessary. Clean with a neutral cleaner.

PRODUCT SPECIFICATIONS

APPEARANCE	Milk white liquid
FILM COLOR	Color free, even after extended use
VISCOSITY @ 77°F cps	Less than A-1 (Gardner-Holt)
PERCENT SOLIDS	22% +/- 0.5%
FLASH POINT	None
pH	7.5 - 8.0
RECOATING TIME	20 minutes
WALK ON TIME	20 - 30 minutes
LEVELING PROPERTIES	Excellent
SCUFF RESISTANCE	Outstanding
BLACK MARK RESISTANCE	Outstanding
ABRASION RESISTANCE	Outstanding
PACKAGING	55- 35- 15 Gallon drums 5 Gallon pails Cases of 6/1 Gallon jugs

SAFETY INFORMATION

Use only as directed. Do not mix with any other chemicals.

CAUTIONS: KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

May cause eye irritation. In case of eye contact, flush with plenty of water for at least 15 minutes. Remove contact lenses, if applicable. If irritation persists, call a physician. If taken internally, do not induce vomiting. Call a physician immediately.