## **DESCRIPTION**

A powerful blend of acids formulated to remove stains from concrete, fiberglass, stone and tile. Removes rust, welding scale, heat marks, light oil and shop soil from carbon steel and iron. It is also effective for removing light oxide and tarnish from copper or copper alloys, brass, bronze and monel.

## **USAGE**

Recommended for industrial, institutional and commercial use. Great for use on fiberglass.

## **DIRECTIONS**

Surface should be prepared by removing loose rust and scale with a wire brush. Apply full strength or diluted with up to three parts of water. Apply with an acid-resistant brush, sprayer, sponge or rag. Allow sufficient time for solution to react. Rinse with clear, cold water and dry. For dip tank application, use plastic lined or rubber lined tanks.

# PRODUCT SPECIFICATIONS

**APPEARANCE** Clear to orange liquid

**ODOR** None

**FLASH POINT** None, non-flammable

pH IN CONCENTRATE 1.0 WEIGHT / Gallon at 77°F 9.5 Lbs. WATER SOLUBILITY 100% **RINSING PROPERTIES** Free Rinsing **ABRASIVES** None

**SHELF LIFE** 1 Year Plus in unopened container

**PACKAGING** 55, 35, 15 Gallon drums

5 Gallon pails

Cases of 6/1 and 4/1 Gallon jugs

#### SAFETY INFORMATION

## KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

CAUTION: This product is destructive to eye and skin tissue on contact. Rubber gloves and goggles should be worn.

Skin, flush immediately with cold water paying particular attention to the skin under the nails. If irritation develops, seek medical attention immediately. Remove and wash all soiled clothing before re-use. *Eyes*, flush thoroughly with large quantities of water at once, and get medical attention immediately. Ingestion, give 2 glasses of water or milk if available and call a physician immediately. DO NOT INDUCE VOMITING.

Read MSDS for additional Cautions.

